

# VEHICLE MAGNET CARE & CLEANING GUIDE



**THANK YOU FOR CHOOSING THE MAGNET SOURCE™ BRAND FLEXIBLE MAGNETIC SHEETING. FOLLOWING THESE GUIDELINES WILL GIVE YOU YEARS OF TROUBLE FREE SERVICE WITH YOUR FLEXIBLE MAGNETIC PURCHASE.**

**SURFACE PREPARATION** The vehicle's surface should be waxed a minimum of 48 hours in advance before applying magnetic sheeting. For new vehicles or newly painted vehicles allow approximately 90 days for the paint to cure before applying magnetic sheeting. Wipe the surface of the vehicle with a clean dry cloth before application and make sure that all grime, dust and dirt has been removed.

**INSTALLATION** It is best to apply flexible magnetic sheeting when the temperature of the magnet is near room temperature or about 68° F. Carefully align one edge of the flexible magnetic sheeting to the vehicle's surface. Allow the remainder of the sheet to apply itself to the vehicle's surface. Do not allow air pockets to form under the sheet. If it is not aligned correctly, be sure to completely remove the sheeting and start over again. Do not pull or drag the sheet to realign it. This can damage or stretch the material.

**REMOVAL** Remove flexible magnetic sheeting periodically to guard against moisture and dirt buildup. On vehicles it is recommended to remove daily to ensure that the vehicle and the magnetic sheet surfaces are clean and free of roadway debris. Dirt trapped between magnetic sheeting and your vehicle can damage its finish.



**CLEANING** Clean flexible magnetic sheeting as well as the surface to be re-applied with a mild detergent, wipe with a soft cloth and allow to dry. This helps to lengthen the life of your flexible product and protects the surface of your vehicle.

**STORAGE** Store flexible magnetic sheeting in a clean dry area. If rolling, roll with printed or non-magnetic side out. Store on end to avoid any flat spots. If storing flat, store on a clean, smooth, flat surface. When stacking, do not stack magnetic side to magnetic side due to the potential of wrinkling caused by improper pole alignment. Do not lay product on the ground because the magnet will attract fine iron particles that are in dirt and asphalt.



**CAUTION** Avoid repainted surfaces, non-metallic body fillers and wood grain vinyl siding.

**BINDING 101**

www.binding101.com • (866)537-2244 • info@buy101.com

Please note that failure to follow this clean and care guide may cause damage to the applied surface and/or the magnet material. Binding101 and The Magnet Source™ will not be held liable for any damage caused by abuse, misuse, or failure to follow this guide.